



R O O T S B L O W E R

高豐魯氏鼓風機

GOLDENTECH ROOTS BLOWER
ROOTS TYPE BLOWER & VACUUM PUMP **CATALOG**



高品質/低噪音三葉魯氏鼓風機

THREE LOBES REDUCE VIBRATION AND NOISE!

高豐三葉式鼓風機是魯氏系列中的一種新產品。本公司以最新的CNC加工技術，製造精確的轉子，所以能提高性能、降低噪音及震動。

GOLDENTECH three lobes blowers are new series roots type blowers. By cnc machine, we made precise rotors to promote performance, lower noise and vibration.

④ 風量、壓力、真空度範圍廣。

1. □ 徑 : 40A ~ 400 A (1.5" ~ 16")
2. 風 量 : 0.5 ~ 360 m³/min
3. 壓 力 : 0 ~ 8000 mmAq
4. 真空度: - 5000 mmAq

④ 風量穩定、壓力變化小。

④ 排出氣體潔淨、不含油污。

④ 構造堅實簡單、保養維護容易。

④ 軸承為機油潤滑、散熱佳、壽命長。



FEATURE

④ Wide range for air Volume、pressure and vacuum.

1. Bore : 40A ~ 400A (1.5" ~ 16")
2. Capacity: 0.5 ~ 360 m³/min
3. Pressure : 0 ~ 8000 mmAq
4. Vacuum : - 5000 mmAq

④ ◆ Stable air flow and less pressure variation.

④ ◆ Clean air not with oil moist.

④ ◆ Construction simple and easy maintenance.

④ ◆ Bearings are all lubricated by oil moist.

為何選擇高豐三葉魯氏鼓風機？


Why You Select GOLDENTECH New Three Lobes Roots Blower?

❏ 較低的能源損耗

三葉式的設計能減少逆流對轉子的壓力，相對地也減少能源的損耗。

❏ LOWER ENERGY CONSUMPTION

Three lobes' design control backflow pressure to rotor so reduce energy consumption.



❏ 較低的噪音

壓力脈衝是主要的噪音源，三葉式鼓風機能有效地降低噪音達5dB。

❏ LOWER NOISE

Pressure pluses are the major noise source of blower. Three lobes' design can efficiently reduce noise by approximately 5dB.

❏ 轉軸壽命延長


由於葉輪傳遞的振動減少，得以延長軸承壽命達20%。

❏ LONGER BEARING LIFE

Less vibration transmitted through the lobe results approximately 20% longer bearing life.

傳統二葉氏鼓風機壓力震幅大，造成震動及噪音縮短軸承、齒輪及其他傳動元件的壽命。

Conventional blowers result pressure pluses and vibration rob power and shorten the life of every bearing, gear and other drive train components.



GT型性能表(壓送式)

GT TYPE PERFORMANCE TABLE (FOR PRESSURE)

TYPE	RPM	Qs(m³/min)				PRESSURE(mmAq)								La(Kw)			
		1000mmAq		2000mmAq		3000mmAq		4000mmAq		5000mmAq		6000mmAq		7000mmAq		8000mmAq	
		Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La
GT-040	1650	0.60	0.19	0.57	0.37	0.54	0.53	0.51	0.67	0.49	0.81	0.48	0.94				
	1800	0.68	0.21	0.64	0.40	0.61	0.57	0.59	0.74	0.57	0.88	0.55	1.02				
	1950	0.75	0.23	0.71	0.43	0.69	0.62	0.66	0.80	0.64	0.96	0.62	1.11				
	2100	0.83	0.24	0.79	0.47	0.76	0.67	0.74	0.86	0.71	1.03	0.70	1.19				
	2250	0.90	0.26	0.86	0.50	0.84	0.72	0.81	0.92	0.79	1.11	0.77	1.28				
	2400	0.97	0.28	0.94	0.53	0.91	0.77	0.88	0.98	0.86	1.18	0.85	1.36				
	2550	1.05	0.30	1.01	0.57	0.98	0.81	0.96	1.04	0.94	1.25	0.92	1.45				
GT-050	850	0.99	0.41	0.79	0.80	0.64	1.16	0.50	1.51	0.38	1.84	0.29	2.15	0.21	2.45	0.15	2.74
	1000	1.31	0.48	1.11	0.94	0.96	1.37	0.82	1.77	0.70	2.16	0.61	2.53	0.53	2.88	0.47	3.22
	1150	1.63	0.56	1.44	1.08	1.28	1.57	1.15	2.04	1.02	2.49	0.93	2.91	0.86	3.32	0.79	3.71
	1300	1.95	0.63	1.76	1.22	1.61	1.78	1.47	2.31	1.34	2.81	1.25	3.29	1.18	3.75	1.12	4.19
	1450	2.27	0.70	2.08	1.36	1.93	1.98	1.79	2.57	1.67	3.13	1.58	3.67	1.50	4.18	1.44	4.67
	1600	2.60	0.77	2.40	1.50	2.25	2.19	2.11	2.84	1.99	3.46	1.90	4.05	1.82	4.61	1.76	5.16
	1750	2.92	0.85	2.72	1.64	2.57	2.39	2.43	3.11	2.31	3.78	2.22	4.43	2.14	5.05	2.08	5.64
GT-065	850	2.07	0.62	1.89	1.21	1.71	1.76	1.55	2.29	1.41	2.78	1.29	3.26	1.19	3.71	1.09	4.15
	1000	2.58	0.73	2.41	1.42	2.22	2.07	2.07	2.69	1.93	3.27	1.81	3.83	1.71	4.37	1.60	4.88
	1150	3.10	0.84	2.93	1.64	2.74	2.38	2.58	3.09	2.45	3.77	2.33	4.41	2.22	5.03	2.12	5.62
	1300	3.62	0.95	3.45	1.85	3.26	2.69	3.10	3.50	2.96	4.26	2.84	4.99	2.74	5.68	2.64	6.35
	1450	4.13	1.06	3.96	2.06	3.77	3.01	3.62	3.90	3.48	4.75	3.36	5.56	3.26	6.34	3.15	7.08
	1600	4.65	1.17	4.48	2.28	4.29	3.32	4.13	4.30	4.00	5.24	3.88	6.14	3.77	6.99	3.67	7.81
	1750	5.17	1.28	5.00	2.49	4.81	3.63	4.65	4.71	4.51	5.73	4.39	6.71	4.29	7.65	4.19	8.55
GT-080	850	3.24	1.12	2.87	2.14	2.54	3.08	2.23	3.94	1.95	4.73	1.70	5.47	1.48	6.15	1.28	6.79
	1000	4.14	1.32	3.77	2.52	3.44	3.62	3.13	4.63	2.85	5.57	2.60	6.44	2.38	7.24	2.18	7.99
	1150	5.04	1.51	4.67	2.90	4.34	4.16	4.03	5.33	3.75	6.40	3.50	7.40	3.28	8.33	3.08	9.19
	1300	5.94	1.71	5.57	3.27	5.24	4.71	4.93	6.02	4.65	7.24	4.40	8.37	4.18	9.41	3.98	10.39
	1450	6.84	1.91	6.47	3.65	6.14	5.25	5.83	6.72	5.55	8.07	5.30	9.33	5.08	10.50	4.88	11.58
	1600	7.74	2.11	7.37	4.03	7.04	5.79	6.73	7.41	6.45	8.91	6.20	10.30	5.98	11.58	5.78	12.78
	1750	8.64	2.30	8.27	4.41	7.94	6.33	7.63	8.11	7.35	9.75	7.10	11.26	6.88	12.67	6.68	13.98
GT-100	850	5.80	1.57	5.19	3.00	4.65	4.31	4.16	5.51	3.74	6.63	3.36	7.66	3.03	8.62	2.74	9.51
	1000	7.06	1.84	6.45	3.53	5.91	5.07	5.42	6.49	5.00	7.80	4.62	9.01	4.29	10.14	4.00	11.19
	1150	8.32	2.12	7.71	4.05	7.17	5.83	6.68	7.46	6.26	8.97	5.88	10.36	5.55	11.66	5.26	12.86
	1300	9.58	2.40	8.97	4.58	8.43	6.59	7.94	8.43	7.52	10.14	7.14	11.71	6.81	13.18	6.52	14.54
	1450	10.84	2.67	10.23	5.11	9.69	7.35	9.20	9.41	8.78	11.31	8.40	13.06	8.07	14.70	7.78	16.22
	1600	12.10	2.95	11.49	5.64	10.95	8.11	10.46	10.38	10.04	12.47	9.66	14.42	9.33	16.22	9.04	17.90
	1750	13.36	3.23	12.75	6.17	12.21	8.87	11.72	11.35	11.30	13.64	10.92	15.77	10.59	17.74	10.30	19.57
GT-125S	750	8.13	2.05	7.43	3.91	6.80	5.62	6.22	7.20	5.72	8.66	5.25	10.01	4.83	11.26	4.46	12.42
	900	10.02	2.46	9.32	4.70	8.69	6.75	8.11	8.64	7.61	10.39	7.14	12.01	6.72	13.51	6.35	14.91
	1050	11.91	2.86	11.21	5.48	10.58	7.87	10.00	10.08	9.50	12.12	9.03	14.01	8.61	15.76	8.24	17.39
	1200	13.80	3.27	13.10	6.26	12.47	9.00	11.89	11.52	11.39	13.85	10.92	16.01	10.50	18.01	10.13	19.88
	1350	15.69	3.68	14.99	7.04	14.36	10.12	13.78	12.96	13.28	15.58	12.81	18.01	12.39	20.27	12.02	22.36
	1500	17.58	4.09	16.88	7.83	16.25	11.25	15.67	14.40	15.17	17.31	14.70	20.01	14.28	22.52	13.91	24.85
	1650	19.47	4.50	18.77	8.61	18.14	12.37	17.56	15.84	17.06	19.04	16.59	22.01	16.17	24.77	15.80	27.33

GT型性能表(壓送式)

GT TYPE PERFORMANCE TABLE (FOR PRESSURE)

TYPE	RPM	Qs(m³/min)				PRESSURE(mmAq)								La(Kw)			
		1000mmAq		2000mmAq		3000mmAq		4000mmAq		5000mmAq		6000mmAq		7000mmAq		8000mmAq	
		Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La
GT-125	750	10.29	2.59	9.42	4.96	8.62	7.13	7.88	9.12	7.25	10.97	6.66	12.67	6.11	14.26	5.65	15.74
	900	12.69	3.11	11.81	5.95	11.01	8.55	10.28	10.95	9.64	13.16	9.05	15.21	8.51	17.11	8.04	18.89
	1050	15.08	3.63	14.20	6.94	13.41	9.98	12.67	12.77	12.03	15.35	11.44	17.74	10.90	19.97	10.44	22.04
	1200	17.48	4.15	16.60	7.93	15.80	11.40	15.07	14.59	14.43	17.55	13.84	20.28	13.29	22.82	12.83	25.18
	1350	19.87	4.66	18.99	8.92	18.19	12.83	17.46	16.42	16.82	19.74	16.23	22.81	15.69	25.67	15.23	28.33
	1500	22.26	5.18	21.39	9.91	20.59	14.25	19.85	18.24	19.22	21.93	18.63	25.35	18.08	28.52	17.62	31.48
	1650	24.66	5.70	23.78	10.90	22.98	15.68	22.25	20.07	21.61	24.13	21.02	27.88	20.48	31.38	20.01	34.63
GT-150	750	13.32	3.34	12.62	6.39	11.98	9.19	11.40	11.76	10.87	14.14	10.39	16.34	10.00	18.39	9.61	20.30
	900	16.40	4.01	15.70	7.67	15.06	11.03	14.49	14.11	13.95	16.97	13.48	19.61	13.09	22.07	12.70	24.36
	1050	19.49	4.68	18.79	8.95	18.15	12.86	17.58	16.47	17.04	19.80	16.57	22.88	16.18	25.75	15.78	28.41
	1200	22.58	5.35	21.88	10.23	21.24	14.70	20.66	18.82	20.13	22.62	19.65	26.15	19.26	29.42	18.87	32.47
	1350	25.66	6.02	24.96	11.50	24.33	16.54	23.75	21.17	23.21	25.45	22.74	29.42	22.35	33.10	21.96	36.53
	1500	28.75	6.68	28.05	12.78	27.41	18.38	26.84	23.52	26.30	28.28	25.83	32.69	25.44	36.78	25.05	40.59
	1650	31.84	7.35	31.14	14.06	30.50	20.21	29.92	25.88	29.39	31.11	28.91	35.96	28.52	40.46	28.13	44.65
GT-200	600	17.01	4.84	15.95	9.27	15.04	13.32	14.21	17.06	13.53	20.51	12.93	23.71	12.40	26.68	11.98	29.45
	750	22.68	6.05	21.62	11.58	20.71	16.65	19.88	21.32	19.20	25.64	18.60	29.64	18.07	33.36	17.65	36.82
	900	28.35	7.27	27.29	13.90	26.38	19.98	25.55	25.59	24.87	30.77	24.27	35.57	23.74	40.03	23.32	44.18
	1050	34.02	8.48	32.96	16.22	32.05	23.32	31.22	29.85	30.54	35.89	29.94	41.49	29.41	46.70	28.99	51.55
	1200	39.69	9.69	38.63	18.53	37.72	26.65	36.89	34.12	36.21	41.02	35.61	47.42	35.08	53.37	34.66	58.91
	1350	45.36	10.90	44.30	20.85	43.39	29.98	42.56	38.38	41.88	46.15	41.28	53.35	40.75	60.04	40.33	66.27
	1500	51.03	12.11	49.97	23.17	49.06	33.31	48.23	42.65	47.55	51.28	46.95	59.28	46.42	66.71	46.00	73.64
GT-200A	600	27.72	7.40	26.22	14.16	24.89	20.35	23.68	26.06	22.58	31.34	21.60	36.23	20.73	40.77	19.98	45.00
	750	36.38	9.25	34.88	17.70	33.55	25.44	32.34	32.58	31.24	39.17	30.26	45.28	29.39	50.96	28.64	56.25
	900	45.05	11.10	43.54	21.24	42.22	30.53	41.00	39.09	39.91	47.01	38.92	54.34	38.06	61.15	37.31	67.50
	1050	53.71	12.95	52.21	24.77	50.88	35.62	49.67	45.61	48.57	54.84	47.59	63.39	46.72	71.34	45.97	78.75
	1200	62.37	14.80	60.87	28.31	59.54	40.71	58.33	52.12	57.23	62.67	56.25	72.45	55.38	81.54	54.63	90.00
	1350	71.03	16.65	69.53	31.85	68.20	45.80	66.99	58.64	65.89	70.51	64.91	81.51	64.04	91.73	63.29	101.2
	1500	79.70	18.50	78.19	35.39	76.87	50.89	75.65	65.16	74.56	78.34	73.57	90.56	72.71	101.9	71.96	112.5
GT-250	600	27.72	7.40	26.22	14.16	24.89	20.35	23.68	26.06	22.58	31.34	21.60	36.23	20.73	40.77	19.98	45.00
	750	36.38	9.25	34.88	17.70	33.55	25.44	32.34	32.58	31.24	39.17	30.26	45.28	29.39	50.96	28.64	56.25
	900	45.05	11.10	43.54	21.24	42.22	30.53	41.00	39.09	39.91	47.01	38.92	54.34	38.06	61.15	37.31	67.50
	1050	53.71	12.95	52.21	24.77	50.88	35.62	49.67	45.61	48.57	54.84	47.59	63.39	46.72	71.34	45.97	78.75
	1200	62.37	14.80	60.87	28.31	59.54	40.71	58.33	52.12	57.23	62.67	56.25	72.45	55.38	81.54	54.63	90.00
	1350	71.03	16.65	69.53	31.85	68.20	45.80	66.99	58.64	65.89	70.51	64.91	81.51	64.04	91.73	63.29	101.2
	1500	79.70	18.50	78.19	35.39	76.87	50.89	75.65	65.16	74.56	78.34	73.57	90.56	72.71	101.9	71.96	112.5
GT-250A	600	39.45	10.36	37.54	18.02	35.93	25.92	34.56	33.71	33.33	41.48	32.19	49.20	31.19	56.8	30.35	64.3
	750	50.92	12.95	49.00	22.52	47.40	32.40	46.02	42.14	44.80	51.85	43.65	61.50	42.66	71.0	41.82	80.4
	900	62.38	15.53	60.47	27.03	58.87	38.88	57.49	50.57	56.27	62.22	55.12	73.80	54.13	85.2	53.29	96.5
	1050	73.85	18.12	71.94	31.53	70.33	45.36	68.96	58.99	67.73	72.59	66.59	86.10	65.59	99.4	64.75	112.6
	1200	85.32	20.71	83.41	36.04	81.80	51.84	80.43	67.42	79.20	82.96	78.06	98.39	77.06	113.6	76.22	128.7
	1350	96.79	23.30	94.87	40.54	93.27	58.32	91.89	75.85	90.67	93.33	89.52	110.7	88.53	127.8	87.69	144.7
	1500	108.3	25.89	106.3	45.05	104.7	64.80	103.4	84.28	102.1	103.7	101.0	123.0	100.0	142.0	99.16	160.8

GT型性能表(壓送式)

GT TYPE PERFORMANCE TABLE (FOR PRESSURE)

TYPE	RPM	Qs(m ³ /min)				PRESSURE(mmAq)								La(Kw)			
		1000mmAq		2000mmAq		3000mmAq		4000mmAq		5000mmAq		6000mmAq		7000mmAq		8000mmAq	
		Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La
GT-300	600	58.94	14.44	55.49	25.88	53.71	37.23	52.04	47.70	50.48	58.83	49.26	68.88	47.59	79.49	46.70	88.83
	750	75.62	18.06	72.17	32.35	70.39	46.54	68.72	59.63	67.16	73.53	65.94	86.10	64.27	99.36	63.38	111.0
	900	92.30	21.67	88.85	38.82	87.07	55.85	85.40	71.55	83.84	88.24	82.62	103.3	80.95	119.2	80.06	133.3
	1050	109.0	25.28	105.5	45.29	103.7	65.16	102.1	83.48	100.5	102.9	99.30	120.5	97.63	139.1	96.74	155.5
	1200	125.7	28.89	122.2	51.76	120.4	74.46	118.8	95.41	117.2	117.7	116.0	137.8	114.3	159.0	113.4	177.7
	1350	142.3	32.50	138.9	58.23	137.1	83.77	135.4	107.3	133.9	132.4	132.7	155.0	131.0	178.8	130.1	199.9
	1500	159.0	36.11	155.6	64.70	153.8	93.08	152.1	119.3	150.6	147.1	149.3	172.2	147.7	198.7	146.8	222.1
GT-300A	600	88.3	21.07	85.0	37.30	82.3	53.64	80.0	71.4	78.1	87.0	76.1	103.1	74.5	119.0	72.5	136.5
	700	104.7	24.58	101.4	43.52	98.7	62.58	96.4	83.3	94.5	101.5	92.5	120.3	90.9	138.9	88.9	159.3
	800	121.1	28.10	117.8	49.74	115.1	71.52	112.8	95.2	110.9	116.0	108.9	137.5	107.3	158.7	105.3	182.1
	900	137.5	31.61	134.2	55.95	131.5	80.46	129.2	107.1	127.3	130.5	125.3	154.7	123.7	178.6	121.7	204.8
	1000	153.9	35.12	150.6	62.17	147.9	89.39	145.6	119.0	143.7	145.0	141.7	171.9	140.1	198.4	138.1	227.6
	1100	170.3	38.63	167.0	68.39	164.3	98.33	162.0	130.9	160.1	159.5	158.1	189.1	156.5	218.2	154.5	250.3
	1200	186.7	42.15	183.4	74.60	180.7	107.3	178.4	142.8	176.5	174.0	174.5	206.3	172.9	238.1	170.9	273.1
GT-350	600	138.3	32.31	133.1	58.00	129.0	83.48	125.2	109.6	121.9	134.1	119.1	160.3	116.3	182.7	113.5	212.3
	700	163.8	37.70	158.6	67.67	154.5	97.39	150.7	127.9	147.4	156.4	144.6	187.1	141.8	213.2	139.0	247.7
	800	189.3	43.08	184.1	77.33	180.0	111.3	176.2	146.2	172.9	178.8	170.1	213.8	167.3	243.7	164.5	283.1
	900	214.8	48.47	209.6	87.00	205.5	125.2	201.7	164.5	198.4	201.1	195.6	240.5	192.8	274.1	190.0	318.5
	1000	240.3	53.85	235.1	96.67	231.0	139.1	227.2	182.7	223.9	223.4	221.1	267.2	218.3	304.6	215.5	353.9
	1100	265.8	59.24	260.6	106.3	256.5	153.0	252.7	201.0	249.4	245.8	246.6	294.0	243.8	335.0	241.0	389.2
	1200	291.3	64.62	286.1	116.0	282.0	167.0	278.2	219.3	274.9	268.1	272.1	320.7	269.3	365.5	266.5	424.6
GT-400	600	236.3	53.28	230.3	95.65	225.5	137.7	221.3	180.8	217.6	221.1	214.1	264.4	211.3	301.4	208.8	350.1
	650	257.4	57.73	251.4	103.6	246.5	149.1	242.3	195.9	238.6	239.5	235.2	286.5	232.3	326.5	229.8	379.3
	700	278.4	62.17	272.4	111.6	267.5	160.6	263.3	210.9	259.6	257.9	256.2	308.5	253.4	351.6	250.8	408.5
	750	299.4	66.61	293.4	119.6	288.6	172.1	284.4	226.0	280.7	276.4	277.2	330.5	274.4	376.7	271.9	437.7
	800	320.4	71.05	314.4	127.5	309.6	183.6	305.4	241.1	301.7	294.8	298.2	352.6	295.4	401.8	292.9	466.8
	850	341.5	75.49	335.5	135.5	330.6	195.0	326.4	256.1	322.7	313.2	319.3	374.6	316.4	426.9	313.9	496.0
	900	362.5	79.93	356.5	143.5	351.6	206.5	347.4	271.2	343.7	331.6	340.3	396.7	337.5	452.0	335.0	525.2

GTV 型性能表 (真空用)

GTV TYPE PERFORMANCE TABLE (FOR VACUUM)

TYPE	RPM	Qs(m³/min)				PRESSURE(mmAq)								La(Kw)			
		-1000mmAq		-2000mmAq		-2500mmAq		-3000mmAq		-3500mmAq		-4000mmAq		-4500mmAq		-5000mmAq	
		Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La
GTV-040	1650	0.60	0.19	0.58	0.37	0.55	0.44	0.51	0.50	0.50	0.56	0.48	0.62				
	1800	0.68	0.21	0.65	0.40	0.62	0.48	0.59	0.55	0.58	0.61	0.55	0.67				
	1950	0.75	0.23	0.72	0.43	0.70	0.51	0.66	0.59	0.65	0.67	0.62	0.73				
	2100	0.83	0.24	0.80	0.47	0.77	0.55	0.74	0.64	0.72	0.72	0.70	0.79				
	2250	0.90	0.26	0.87	0.50	0.85	0.59	0.81	0.69	0.80	0.77	0.77	0.84				
	2400	0.97	0.28	0.95	0.53	0.92	0.63	0.88	0.73	0.87	0.82	0.85	0.90				
	2550	1.05	0.30	1.02	0.57	0.99	0.67	0.96	0.78	0.95	0.87	0.92	0.95				
GTV-050	850	0.99	0.41	0.82	0.80	0.72	0.98	0.61	1.16	0.51	1.34	0.36	1.51	0.27	1.67	0.14	1.84
	1000	1.31	0.48	1.14	0.94	1.04	1.16	0.93	1.37	0.83	1.57	0.69	1.77	0.59	1.97	0.46	2.16
	1150	1.63	0.56	1.47	1.08	1.36	1.33	1.25	1.57	1.15	1.81	1.01	2.04	0.91	2.27	0.79	2.49
	1300	1.95	0.63	1.79	1.22	1.69	1.50	1.58	1.78	1.48	2.05	1.33	2.31	1.24	2.56	1.11	2.81
	1450	2.27	0.70	2.11	1.36	2.01	1.68	1.90	1.98	1.80	2.28	1.65	2.57	1.56	2.86	1.43	3.13
	1600	2.60	0.77	2.43	1.50	2.33	1.85	2.22	2.19	2.12	2.52	1.97	2.84	1.88	3.15	1.75	3.46
	1750	2.92	0.85	2.75	1.64	2.65	2.02	2.54	2.39	2.44	2.75	2.29	3.11	2.20	3.45	2.07	3.78
GTV-065	850	2.09	0.66	1.91	1.28	1.80	1.58	1.68	1.87	1.55	2.15	1.41	2.42	1.26	2.69	1.09	2.95
	1000	2.60	0.78	2.43	1.51	2.32	1.86	2.19	2.20	2.07	2.53	1.92	2.85	1.77	3.16	1.60	3.47
	1150	3.12	0.89	2.95	1.73	2.84	2.14	2.71	2.53	2.58	2.91	2.44	3.28	2.29	3.64	2.12	3.99
	1300	3.64	1.01	3.46	1.96	3.35	2.41	3.23	2.86	3.10	3.29	2.96	3.71	2.81	4.11	2.64	4.51
	1450	4.15	1.13	3.98	2.19	3.87	2.69	3.74	3.19	3.62	3.67	3.47	4.13	3.32	4.59	3.15	5.03
	1600	4.67	1.24	4.50	2.41	4.39	2.97	4.26	3.52	4.13	4.05	3.99	4.56	3.84	5.06	3.67	5.55
	1750	5.19	1.36	5.01	2.64	4.90	3.25	4.78	3.85	4.65	4.42	4.51	4.99	4.36	5.54	4.19	6.08
GTV-080	850	3.24	1.12	2.83	2.14	2.60	2.62	2.36	3.08	2.10	3.52	1.83	3.94	1.54	4.34	1.23	4.73
	1000	4.14	1.32	3.73	2.52	3.50	3.08	3.26	3.62	3.00	4.14	2.73	4.63	2.44	5.11	2.13	5.57
	1150	5.04	1.51	4.63	2.90	4.40	3.54	4.16	4.16	3.90	4.76	3.63	5.33	3.34	5.88	3.03	6.40
	1300	5.94	1.71	5.53	3.27	5.30	4.01	5.06	4.71	4.80	5.38	4.53	6.02	4.24	6.64	3.93	7.24
	1450	6.84	1.91	6.43	3.65	6.20	4.47	5.96	5.25	5.70	6.00	5.43	6.72	5.14	7.41	4.83	8.08
	1600	7.74	2.11	7.33	4.03	7.10	4.93	6.86	5.79	6.60	6.62	6.33	7.41	6.04	8.18	5.73	8.91
	1750	8.64	2.30	8.23	4.41	8.00	5.39	7.76	6.33	7.50	7.24	7.23	8.11	6.94	8.94	6.63	9.75
GTV-100	850	5.79	1.57	5.19	3.00	4.85	3.67	4.48	4.31	4.09	4.92	3.67	5.51	3.22	6.08	2.74	6.63
	1000	7.05	1.84	6.45	3.53	6.11	4.31	5.74	5.07	5.35	5.79	4.93	6.49	4.48	7.15	4.00	7.80
	1150	8.31	2.12	7.71	4.05	7.37	4.96	7.00	5.83	6.61	6.66	6.19	7.46	5.74	8.23	5.26	8.97
	1300	9.57	2.40	8.97	4.58	8.63	5.61	8.26	6.59	7.87	7.53	7.45	8.43	7.00	9.30	6.52	10.14
	1450	10.83	2.67	10.23	5.11	9.89	6.25	9.52	7.35	9.13	8.40	8.71	9.41	8.26	10.37	7.78	11.31
	1600	12.09	2.95	11.49	5.64	11.15	6.90	10.78	8.11	10.39	9.27	9.97	10.38	9.52	11.45	9.04	12.47
	1750	13.35	3.23	12.75	6.17	12.41	7.55	12.04	8.87	11.65	10.14	11.23	11.35	10.78	12.52	10.30	13.64
GTV-125 S	750	8.13	2.05	7.35	3.91	6.93	4.79	6.48	5.63	6.01	6.43	5.53	7.20	5.00	7.94	4.46	8.66
	900	10.02	2.46	9.24	4.70	8.82	5.75	8.37	6.75	7.90	7.72	7.42	8.64	6.89	9.53	6.35	10.39
	1050	11.91	2.86	11.13	5.48	10.71	6.70	10.26	7.88	9.79	9.00	9.31	10.08	8.78	11.12	8.24	12.12
	1200	13.80	3.27	13.02	6.26	12.60	7.66	12.15	9.00	11.68	10.29	11.20	11.52	10.67	12.71	10.13	13.85
	1350	15.69	3.68	14.91	7.04	14.49	8.62	14.04	10.13	13.57	11.57	13.09	12.96	12.56	14.30	12.02	15.59
	1500	17.58	4.09	16.80	7.83	16.38	9.58	15.93	11.25	15.46	12.86	14.98	14.40	14.45	15.89	13.91	17.32
	1650	19.47	4.50	18.69	8.61	18.27	10.53	17.82	12.38	17.35	14.14	16.87	15.84	16.34	17.48	15.80	19.05

GTV 型性能表 (真空用)

GTV TYPE PERFORMANCE TABLE (FOR VACUUM)

TYPE	RPM	Qs(m³/min)				PRESSURE(mmAq)								La(Kw)			
		-1000mmAq		-2000mmAq		-2500mmAq		-3000mmAq		-3500mmAq		-4000mmAq		-4500mmAq		-5000mmAq	
		Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La
GTV-125	750	10.29	2.59	9.30	4.96	8.78	6.06	8.20	7.13	7.61	8.14	7.01	9.12	6.34	10.06	5.65	10.97
	900	12.69	3.11	11.70	5.95	11.17	7.28	10.60	8.55	10.01	9.77	9.40	10.95	8.73	12.07	8.04	13.16
	1050	15.08	3.63	14.09	6.94	13.57	8.49	12.99	9.98	12.40	11.40	11.79	12.77	11.12	14.09	10.44	15.35
	1200	17.48	4.15	16.49	7.93	15.96	9.70	15.39	11.40	14.79	13.03	14.19	14.59	13.52	16.10	12.83	17.55
	1350	19.87	4.66	18.88	8.92	18.35	10.92	17.78	12.83	17.19	14.66	16.58	16.42	15.91	18.11	15.23	19.74
	1500	22.26	5.18	21.27	9.91	20.75	12.13	20.17	14.25	19.58	16.29	18.98	18.24	18.31	20.12	17.62	21.93
	1650	24.66	5.70	23.67	10.90	23.14	13.34	22.57	15.68	21.98	17.92	21.37	20.07	20.70	22.14	20.01	24.13
GTV-150	750	13.32	3.34	12.55	6.39	12.14	7.82	11.69	9.19	11.20	10.50	10.68	11.76	10.13	12.97	9.55	14.14
	900	16.40	4.01	15.64	7.67	15.23	9.38	14.78	11.03	14.28	12.60	13.77	14.11	13.21	15.57	12.64	16.97
	1050	19.49	4.68	18.73	8.95	18.32	10.95	17.86	12.86	17.37	14.70	16.86	16.47	16.30	18.16	15.72	19.80
	1200	22.58	5.35	21.81	10.23	21.40	12.51	20.95	14.70	20.46	16.80	19.94	18.82	19.39	20.76	18.81	22.62
	1350	25.66	6.02	24.90	11.50	24.49	14.07	24.04	16.54	23.54	18.90	23.03	21.17	22.47	23.35	21.90	25.45
	1500	28.75	6.68	27.99	12.78	27.58	15.64	27.12	18.38	26.63	21.00	26.12	23.52	25.56	25.95	24.98	28.28
	1650	31.84	7.35	31.08	14.06	30.66	17.20	30.21	20.21	29.72	23.10	29.20	25.88	28.65	28.54	28.07	31.11
GTV-200	600	17.01	4.84	15.99	9.27	15.42	11.34	14.86	13.32	14.21	15.23	13.49	17.06	12.78	18.82	11.98	20.51
	750	22.68	6.05	21.66	11.58	21.09	14.17	20.53	16.65	19.88	19.04	19.16	21.32	18.45	23.52	17.65	25.64
	900	28.35	7.27	27.33	13.90	26.76	17.01	26.20	19.98	25.55	22.84	24.83	25.59	24.12	28.23	23.32	30.77
	1050	34.02	8.48	33.00	16.22	32.43	19.84	31.87	23.32	31.22	26.65	30.50	29.85	29.79	32.93	28.99	35.89
	1200	39.69	9.69	38.67	18.53	38.10	22.67	37.54	26.65	36.89	30.46	36.17	34.12	35.46	37.64	34.66	41.02
	1350	45.36	10.90	44.34	20.85	43.77	25.51	43.21	29.98	42.56	34.26	41.84	38.38	41.13	42.34	40.33	46.15
	1500	51.03	12.11	50.01	23.17	49.44	28.34	48.88	33.31	48.23	38.07	47.51	42.65	46.80	47.05	46.00	51.28
GTV-200A	600	27.72	7.40	26.22	14.16	25.35	17.32	24.43	20.35	23.45	23.27	22.35	26.06	21.19	28.75	19.98	31.34
	750	36.38	9.25	34.88	17.70	34.01	21.65	33.09	25.44	32.11	29.08	31.01	32.58	29.86	35.94	28.64	39.17
	900	45.05	11.10	43.54	21.24	42.68	25.98	41.75	30.53	40.77	34.90	39.67	39.09	38.52	43.13	37.31	47.01
	1050	53.71	12.95	52.21	24.77	51.34	30.31	50.42	35.62	49.43	40.72	48.34	45.61	47.18	50.31	45.97	54.84
	1200	62.37	14.80	60.87	28.31	60.00	34.64	59.08	40.71	58.10	46.53	57.00	52.12	55.84	57.50	54.63	62.67
	1350	71.03	16.65	69.53	31.85	68.66	38.97	67.74	45.80	66.76	52.35	65.66	58.64	64.51	64.69	63.29	70.51
	1500	79.7	18.50	78.2	35.39	77.3	43.30	76.4	50.89	75.4	58.16	74.3	65.16	73.17	71.88	71.96	78.34
GTV-250	600	27.72	7.40	26.22	14.16	25.35	17.32	24.43	20.35	23.45	23.27	22.35	26.06	21.19	28.75	19.98	31.34
	750	36.38	9.25	34.88	17.70	34.01	21.65	33.09	25.44	32.11	29.08	31.01	32.58	29.86	35.94	28.64	39.17
	900	45.05	11.10	43.54	21.24	42.68	25.98	41.75	30.53	40.77	34.90	39.67	39.09	38.52	43.13	37.31	47.01
	1050	53.71	12.95	52.21	24.77	51.34	30.31	50.42	35.62	49.43	40.72	48.34	45.61	47.18	50.31	45.97	54.84
	1200	62.37	14.80	60.87	28.31	60.00	34.64	59.08	40.71	58.10	46.53	57.00	52.12	55.84	57.50	54.63	62.67
	1350	71.03	16.65	69.53	31.85	68.66	38.97	67.74	45.80	66.76	52.35	65.66	58.64	64.51	64.69	63.29	70.51
	1500	79.70	18.50	78.19	35.39	77.33	43.30	76.40	50.89	75.42	58.16	74.32	65.16	73.17	71.88	71.96	78.34
GTV-250A	600	39.31	10.34	37.13	17.81	35.63	21.47	34.37	25.13	33.01	28.89	31.74	32.48	30.37	35.83	28.82	39.97
	750	50.78	12.92	48.60	22.26	47.09	26.84	45.84	31.41	44.48	36.12	43.21	40.59	41.83	44.78	40.29	49.97
	900	62.25	15.50	60.07	26.72	58.56	32.21	57.31	37.70	55.95	43.34	54.68	48.71	53.30	53.74	51.76	59.96
	1050	73.71	18.09	71.53	31.17	70.03	37.57	68.77	43.98	67.41	50.57	66.14	56.83	64.77	62.70	63.22	69.95
	1200	85.18	20.67	83.00	35.62	81.50	42.94	80.24	50.26	78.88	57.79	77.61	64.95	76.24	71.65	74.69	79.95
	1350	96.65	23.26	94.47	40.07	92.96	48.31	91.71	56.55	90.35	65.01	89.08	73.07	87.70	80.61	86.16	89.94
	1500	108.1	25.84	105.9	44.53	104.4	53.68	103.2	62.83	101.8	72.24	100.5	81.19	99.17	89.57	97.63	99.93


GTV 型性能表 (真空用)

GTV TYPE PERFORMANCE TABLE (FOR VACUUM)


TYPE	RPM	Qs(m³/min)				PRESSURE(mmAq)								La(Kw)			
		-1000mmAq		-2000mmAq		-2500mmAq		-3000mmAq		-3500mmAq		-4000mmAq		-4500mmAq		-5000mmAq	
		Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La	Qs	La
GTV-300	600	58.94	14.25	56.27	27.26	54.82	33.35	53.15	39.19	51.49	44.80	49.71	50.18	47.70	55.36	45.70	60.34
	750	75.62	17.81	72.95	34.07	71.50	41.69	69.83	48.99	68.17	56.00	66.39	62.72	64.38	69.20	63.38	75.42
	900	92.30	21.38	89.63	40.89	88.18	50.02	86.51	58.79	84.85	67.20	83.07	75.27	81.06	83.04	79.06	90.51
	1050	109.0	24.94	106.3	47.70	104.9	58.36	103.2	68.58	101.5	78.40	99.75	87.81	97.74	96.88	95.74	105.6
	1200	125.7	28.50	123.0	54.52	121.5	66.70	119.9	78.38	118.2	89.60	116.4	100.4	114.4	110.7	112.4	120.7
	1350	142.3	32.06	139.7	61.33	138.2	75.04	136.6	88.18	134.9	100.8	133.1	112.9	131.1	124.6	129.1	135.8
	1500	159.0	35.63	156.3	68.15	154.9	83.37	153.2	97.98	151.6	112.0	149.8	125.4	147.8	138.4	145.8	150.8
GTV-300A	600	88.2	21.04	84.4	36.86	82.0	44.47	79.7	53.34	77.7	60.6	75.3	68.0	72.5	77.0	69.0	84.7
	700	104.6	24.54	100.9	43.01	98.4	51.88	96.2	62.23	94.1	70.6	91.8	79.4	89.0	89.8	85.5	98.9
	800	121.0	28.05	117.3	49.15	114.8	59.29	112.6	71.12	110.5	80.7	108.2	90.7	105.4	102.7	101.9	113.0
	900	137.5	31.56	133.7	55.29	131.3	66.70	129.1	80.00	127.0	90.8	124.7	102.0	121.8	115.5	118.4	127.1
	1000	153.9	35.06	150.2	61.44	147.7	74.11	145.5	88.89	143.4	100.9	141.1	113.4	138.3	128.3	134.8	141.2
	1100	170.3	38.57	166.6	67.58	164.1	81.52	161.9	97.78	159.9	111.0	157.5	124.7	154.7	141.2	151.2	155.3
	1200	186.8	42.07	183.0	73.72	180.6	88.93	178.4	106.7	176.3	121.1	174.0	136.1	171.1	154.0	167.7	169.5
GTV-350	600	138.1	32.72	132.3	57.32	128.5	69.15	124.7	82.94	121.4	94.16	117.9	105.8	113.5	119.8	107.9	131.7
	700	163.6	38.17	157.8	66.87	154.0	80.67	150.2	96.77	146.9	109.9	143.4	123.4	139.0	139.7	133.4	153.7
	800	189.1	43.63	183.3	76.42	179.5	92.20	175.7	110.6	172.4	125.6	168.9	141.1	164.5	159.7	158.9	175.7
	900	214.6	49.08	208.8	85.97	205.0	103.7	201.2	124.4	197.9	141.2	194.4	158.7	190.0	179.6	184.4	197.6
	1000	240.1	54.53	234.3	95.53	230.5	115.2	226.7	138.2	223.4	156.9	219.9	176.3	215.5	199.6	209.9	219.6
	1100	265.6	59.99	259.8	105.1	256.0	126.8	252.2	152.1	248.9	172.6	245.4	193.9	241.0	219.6	235.4	241.5
	1200	291.1	65.44	285.3	114.6	281.5	138.3	277.7	165.9	274.4	188.3	270.9	211.6	266.5	239.5	260.9	263.5
GTV-400	600	236.3	52.99	228.3	95.77	224.6	117.3	219.5	137.9	216.6	159.0	212.4	180.5	209.4	212.8	203.5	223.0
	650	257.4	57.40	249.4	103.8	245.6	127.1	240.5	149.4	237.6	172.3	233.4	195.5	230.5	230.5	224.6	241.6
	700	278.4	61.82	270.4	111.7	266.6	136.8	261.6	160.9	258.6	185.5	254.4	210.6	251.5	248.3	245.6	260.2
	750	299.4	66.23	291.4	119.7	287.6	146.6	282.6	172.4	279.7	198.8	275.4	225.6	272.5	266.0	266.6	278.8
	800	320.4	70.65	312.5	127.7	308.7	156.4	303.6	183.9	300.7	212.0	296.5	240.7	293.5	283.7	287.6	297.3
	850	341.5	75.07	333.5	135.7	329.7	166.2	324.6	195.4	321.7	225.3	317.5	255.7	314.6	301.5	308.7	315.9
	900	362.5	79.48	354.5	143.7	350.7	175.9	345.7	206.9	342.7	238.5	338.5	270.7	335.6	319.2	329.7	334.5

GT 壓送式性能曲線 PRESSURE PERFORMANCE CURVE


GT-040




GT-100




GT-050




GT-125S




GT-065




GT-125



GT-080




GT-150




GT 壓送式性能曲線 PRESSURE PERFORMANCE CURVE


GT-200




GT-300




GT-200A




GT-300A




GT-250




GT-350











GT-250A











GT-400



GTV 真空型性能曲線 VACUUM PERFORMANCE CURVE



GTV 真空型性能曲線 VACUUM PERFORMANCE CURVE



風量計算及性能曲線使用方法

HOW TO USE PERFORMANCE CHART

1. 鼓風機的風量可以下型式表示:

- (1) 標準狀態STP風量(Qs):溫度20℃, 絕對壓力10332mmAq, 相對濕度65%。
- (2) 基準狀態NTP風量(Qn):溫度0℃, 絕對壓力10332mmAq, 相對濕度0%。

2. 性能表所示風量是標準狀態STP之吸入風量。

3. 性能表所示壓力是鼓風機之靜壓。

4. 風量在不同壓力、溫度下的轉換公式

$$Q_2 = Q_1 \cdot \frac{P_1}{P_2} \cdot \frac{T_2}{T_1}$$

Q1(m³/min): 在絕對壓力P₁(mmAq), 絕對溫度T₁(°K)下之風量。

Q2(m³/min): 在絕對壓力P₂(mmAq), 絕對溫度T₂(°K)下之風量。

5. 靜壓的換算

(1) 壓送的場合

$$P_s = \left(\frac{10332 + P_2}{10332 + P_1} - 1 \right) \cdot 10332$$

(2) 真空的場合

$$P_s = \left(\frac{10332 + P_1}{10332 + P_2} - 1 \right) \cdot 10332$$

P₁:入口靜壓 P₂:出口靜壓 P_s:型錄之靜壓

6. 範例

操作條件 : 風量 5.16 m³/min
入口靜壓 -500 mmAq
出口靜壓 +4260 mmAq
入口溫度 40℃

選用 : 入口風量5.16m³/min, 必須換算成標準狀態(STP)時的風量。

$$Q = 5.16 \cdot \frac{10332 - 500}{10332} \cdot \frac{273 + 20}{273 + 40} = 4.60 \text{ m}^3/\text{min}$$

靜壓換算

$$P_s = \left(\frac{10332 + 4260}{10332 - 500} - 1 \right) \cdot 10332 = 5000 \text{ mmAq}$$

查性能曲線可選擇LT-80、轉速1300RPM, 馬力10HP。

7. 相同風量涵蓋二機種時, 小機種具有經濟性, 大機種則有較低的轉速即低噪音的優點, 請參看噪音表。

1. AIR VOLUME IS GENERAL SHOWN IN TERMS OF

- (1) STANDARD STATE (Qs): AT 20°C, 10332mmAq, AND RH. 65%。
- (2) NORMAL STATE (Qn): AT 0°C, 10332mmAq, AND RH. 0%。

2. PERFORMANCE TABLE SHOWN THE CAPACITY AT THE STANDARD SUCTION STATE.

3. PERFORMANCE TABLE SHOWN THE PRESSURE AT THE STATIC PRESSURE.

4. VOLUME CONVERSION FORMULA

$$Q_2 = Q_1 \cdot \frac{P_1}{P_2} \cdot \frac{T_2}{T_1}$$

Q₁(m³/min): AIR VOLUME IN P₁(mmAq), T₁(°K)。

Q₂(m³/min): AIR VOLUME IN P₂(mmAq), T₂(°K)。

5. PRESSURE CONVERSION FORMULA

(1) FOR PRESSURE

$$P_s = \left(\frac{10332 + P_2}{10332 + P_1} - 1 \right) \cdot 10332$$

(2) FOR VACUUM

$$P_s = \left(\frac{10332 + P_1}{10332 + P_2} - 1 \right) \cdot 10332$$

P₁: SUCTION STATIC PRESSURE

P₂: DISCHARGE STATIC PRESSURE

P_s: STATIC PRESSURE IN CATALOG

6. EXAMPLE

OPERATING SPECIFICATIONS:

AIR VOLUME 5.16 m³/min
SUCTION STATIC PRESSURE -500 mmAq
DISCHARGE STATIC PRESSURE +4260 mmAq
SUCTION TEMPERATURE 40℃

CHOICE: AIR VOLUME(5.16 m³/min) CONVERTS TO STP STATE

$$Q = 5.16 \cdot \frac{10332 - 500}{10332} \cdot \frac{273 + 20}{273 + 40} = 4.60 \text{ m}^3/\text{min}$$

STATIC PRESSURE CHANGED TO

$$P_s = \left(\frac{10332 + 4260}{10332 - 500} - 1 \right) \cdot 10332 = 5000 \text{ mmAq}$$

SEE THE PERFORMANCE TABLE, YOU COULD FIND LT-80、1300RPM、10HP FITS THE SPECIFICATIONS。

7. AS THE SELECTION COVERS TWO MODELS, YOU MAY SELECT THE SMALLER FOR ECONOMIC, BUT YOU CHOICE THE BIGGER WITH THE ADVANTAGE OF LOWER RPM. PLEASE REFER TO NOISE CHART IN THE FOLLOWING PAGE。











噪音表 NOISE LEVEL OF BLOWER

噪音資料係距離鼓風機1m及附標準消音器所測量的平均值。







NOISE LEVEL MEASURED AT DISTANCE 1 METER FOR THE BLOWER FITTED WITH STANDARD SILENCER.

噪音值因加裝管路的長度及周圍的環境狀況而有所改變。

NOISE LEVEL MAYBE DIFFERENT ACCORDING TO THE EXTEND PIPE LENGTH AND AMBIENT CONDITION.



噪音表 NOISE LEVEL OF BLOWER



單位換算

UNITS CONVERSION

壓力 PRESSURE

	mbar	Pa	atm	lbf/in ²	kgf/cm ²	in-Hg	mmAq
1 mbar	1	10 ²	9.869x10 ⁻⁴	1.45x10 ⁻²	1.02x10 ⁻³	2.953x10 ⁻²	10.197
1 Pa	0.01	1	9.869x10 ⁻⁶	1.45x10 ⁻⁴	1.02x10 ⁻⁵	2.953x10 ⁻⁴	0.102
1 atm	1.013x10 ³	1.013x10 ⁵	1	14.7	1.033	29.92	1.033x10 ⁴
1 lbf/in ²	68.95	6.895x10 ²	6.805x10 ⁻²	1	7.03x10 ⁻²	2.036	7.03x10 ²
1 kgf/cm ²	9.807x10 ²	9.807x10 ⁴	0.968	14.22	1	28.96	10 ⁴
1 in-Hg	33.86	3.386x10 ³	3.342x10 ⁻²	0.491	3.45x10 ⁻²	1	3.45x10 ²
1 mmAq	9.807x10 ⁻²	9.807	9.677x10 ⁻⁵	1.42x10 ⁻³	10 ⁻⁴	2.896x10 ⁻³	1


風量 CAPACITY

	m ³ /min	m ³ /hr	l/min	ft ³ /min
1 m ³ /min	1	60	1000	35.31
1 m ³ /hr	0.017	1	16.67	0.589
1 l/min	0.001	0.06	1	0.035
1 ft ³ /min	0.028	1.699	28.32	1


功率 POWER

	kg-m/sec	KW	HP	PS
1 kg-m/sec	1	0.01	0.013	0.013
1 kW	101.97	1	1.341	1.360
1 HP	76.038	0.746	1	1.014
1 PS	75	0.736	0.986	1

外形尺寸圖 OUTLINE DIMENSIONS




GT-025~040




UNITS : mm

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	T	Wt. (Kg)
GT-025	135	145	120	15	350	54	13	10	12	340	40	43	50	400	15	135	1	20
GT-040	162	185	120	15	350	80	15	10	12	340	40	43	50	400	15	135	1.5	25

◆ 表列重量僅為主機重量 (WT. FOR MAINBODY)



GT-050~065




UNITS : mm

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	T	Wt. (Kg)
GT-050	240	270	168	20	370	125	15	15	15	356	90	75	18	734	15	200	2	76
GT-065	280	290	173	20	370	210	15	15	15	356	95	75	18	734	15	200	2.5	94

◆ 表列重量僅為主機重量 (WT. FOR MAINBODY)

GT-080~150




UNITS : mm

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	T	Wt. (Kg)
GT-080	315	375	220	20	450	190	25	19	15	395	102	75	18	934	25	250	3	167
GT-100	365	425	220	20	450	290	25	19	15	395	115	75	18	934	25	250	4	193
GT-125S	405	445	265	25	605	230	25	19	19	475	145	100	20	1190	25	350	5	319
GT-125	445	485	300	25	605	320	25	19	19	515	155	100	20	1190	25	350	5	353
GT-150	500	540	300	25	605	425	25	19	19	515	155	100	20	1190	25	350	6	418

◆ 表列重量僅為主機重量 (WT. FOR MAINBODY)

GT-200~300





UNITS : mm

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	T	Wt. (Kg)
GT-200	515	495	363	30	730	270	35	23	19	650	190	125	200	550	40	550	8	720
GT-200A	605	595	363	30	730	460	35	23	19	665	190	125	200	550	40	550	8	897
GT-250	605	595	388	30	730	460	35	23	19	675	225	125	200	550	40	550	10	913
GT-250A	778	678	500	40	850	650	65	27	24	875	250	200	200	800	55	620	10	1665
GT-300	900	805	500	40	1120	650	65	27	24	875	250	200	200	800	55	620	12	2010
GT-300A	954	840	505	40	1300	660	60	27	24	930	243	200	200	800	60	680	12	3200

◆ 表列重量僅為主機重量 (WT. FOR MAINBODY)

GT-350





UNITS : mm

MODEL	A	B	C	D	E	F	F1	G	G1	H	J	K	L	M	N	P	R	S	T	Wt. (Kg)
GT-350	965	1065	830	40	1400	570	354	133	35	241	24	1020	278	250	300	600	800	830	14	4100

◆ 表列重量僅為主機重量 (WT. FOR MAINBODY)

GT-400




UNITS : mm

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	T	Wt. (Kg)
GT-400	1043	1147	945	40	1400	930	60	35	24	1215	315	250	300	600	800	435	16	4650

◆ 表列重量僅為主機重量 (WT. FOR MAINBODY)

構造圖 & 材質表 STRUCTURE & MATERIAL LIST




NO.	NAME	MATERIAL	NO.	NAME	MATERIAL
1.	Gear case 齒輪箱	FC250	11.	Seal case 油封座	FC250
2.	Oil splash 甩油片	SS400	12.	Pulley 皮帶輪	FC250
3.	Oil plug 加油塞	S45C	13.	Nut 螺帽	SS400
4.	Bearing 軸承	SUJ2	14.	Seal 油封	NBR
5.	Bearing case 軸承座	FC250	15.	Nut 螺帽	SS400
6.	Labyrinth seal 軸封	SS400	16.	Shaft 主軸	SCM440
7.	Eye bolt 吊環	S45C	17.	Main casing 主體	FC250
8.	Rotor 葉輪	FC250	18.	Timing gear 正齒輪	SCM415
9.	Side cover 側蓋	FC250	19.	Oil drain 洩油塞	S45C
10.	Oil case 油箱	FC250	20.	Oil gauge 油鏡	S45C

安裝圖 INSTALLATIONS

A. 壓送配管的場合 (FOR PRESSURE)




B. 真空配管的場合 (FOR VACUUM)




附屬配件 ACCESSORIES

室外入口消音器 OUTDOOR SILENCER UNITS : mm




MODEL	A	B	C	適用機型
O-050	680	50	165	GT-050
O-065	680	65	165	GT-065
O-080	800	80	216	GT-080
O-100	820	100	267	GT-100
O-125	1300	125	350	GT-125
O-150	1300	150	350	GT-150
O-200	2030	200	525	GT-200
O-250	2030	250	600	GT-250
O-300	2240	300	700	GT-300
O-350	2570	350	800	GT-350
O-400	2570	400	800	GT-400

室內入口消音器 INDOOR SILENCER UNITS : mm




MODEL	A	B	C	適用機型
I-050	680	50	165	GT-050
I-065	680	65	165	GT-065
I-080	800	80	216	GT-080
I-100	820	100	267	GT-100
I-125	1300	125	350	GT-125
I-150	1300	150	350	GT-150
I-200	2030	200	525	GT-200
I-250	2030	250	600	GT-250
I-300	2240	300	700	GT-300
I-350	2570	350	800	GT-350
I-400	2570	400	800	GT-400

出口消音器 DISCHARGE SILENCER UNITS : mm




MODEL	A	B	C	適用機型
D-050	660	50	165	GT-050
D-065	660	65	165	GT-065
D-080	760	80	216	GT-080
D-100	760	100	267	GT-100
D-125	1190	125	350	GT-125
D-150	1190	150	350	GT-150
D-200	1735	200	525	GT-200
D-250	1735	250	600	GT-250
D-300	1735	300	700	GT-300
D-350	2230	350	800	GT-350
D-400	2230	400	800	GT-400

臥式室內入口消音器 HORIZONTAL SILENCER UNITS : mm




MODEL	A	B	C	適用機型
RO-050	580	165	120	GT-050
RO-065	580	165	120	GT-065
RO-080	700	216	150	GT-080
RO-100	700	267	150	GT-100
RO-125	1200	350	150	GT-125
RO-150	1200	350	150	GT-150
RO-200	1880	525	400	GT-200
RO-250	1880	600	400	GT-250
RO-300	2090	700	400	GT-300
RO-350	2420	800	400	GT-350
RO-400	2420	800	400	GT-400

三通管 "T" JOINT




MODEL	A	B	C	適用機型
T-050	40	50	150	GT-050
T-065	40	65	150	GT-065
T-080	40	80	165	GT-080
T-100	40	100	165	GT-100
T-125	50	125	205	GT-125
T-150	50	150	210	GT-150
T-200	50	200	265	GT-200

三通管 "T" JOINT




MODEL	A	B	L	適用機型
T-250	80	250	295	GT-250
T-300	80	300	350	GT-300
T-350	125	350	400	GT-350
T-400	125	400	500	GT-400

安全閥 RELIEF VALVE




MODEL	A	B	C	適用機型
R-038	132	1.5"	26	GT-050~100
R-050	150	2"	28	GT-125~200

安全閥 RELIEF VALVE




MODEL	A	B	C	適用機型
R-080	485	3"	80	GT-250~300
R-125	485	5"	125	GT-350~400

伸縮接頭 FLEXIBLE JOINT



MODEL	A	B	L	適用機型
JF-050	50	155	150	GT-050
JF-065	65	175	150	GT-065
JF-080	80	185	150	GT-080
JF-100	100	210	150	GT-100
JF-125	125	250	150	GT-125
JF-150	150	280	150	GT-150
JF-200	200	330	200	GT-200
JF-250	250	400	200	GT-250
JF-300	300	445	200	GT-300
JF-350	350	490	230	GT-350
JF-400	400	560	250	GT-400


防震接頭 FLEXIBLE JOINT



MODEL	A	B	L	適用機型
F-050	50	155	105	GT-050
F-065	65	175	115	GT-065
F-080	80	185	130	GT-080
F-100	100	210	135	GT-100
F-125	125	250	170	GT-125
F-150	150	280	180	GT-150
F-200	200	330	205	GT-200
F-250	250	400	240	GT-250
F-300	300	445	260	GT-300
F-350	350	490	265	GT-350
F-400	400	560	265	GT-400

附屬配件 ACCESSORIES


入口消音器 SHORT SILENCER



UNITS : mm

MODEL	A	B	適用機型
S-50	320	176	GT-50
S-65	320	176	GT-65


90°彎頭 90° ELBOW



UNITS : mm

MODEL	A	B	適用機型
HE-050	83	121	GT-050
HE-065	103	103	GT-065
HE-080	122	122	GT-080
HE-100	160	160	GT-100
HE-125	199	199	GT-125
HE-150	237	237	GT-150
HE-200	313	313	GT-200
HE-250	389	389	GT-250
HE-300	465	465	GT-300
HE-350	541	541	GT-350
HE-400	618	618	GT-400


真空過濾筒 FILTER TANK



UNITS : mm

MODEL	A	B	C	E	H
B-050	395	50	180	210	530
B-065	395	65	180	210	530
B-080	480	80	210	270	670
B-100	480	100	210	270	670


真空過濾筒 FILTER TANK



UNITS : mm

MODEL	A	B	C	E	H
B-125	760	125	270	330	770
B-150	760	150	270	330	770
B-200	920	200	370	492	1140
B-250	1092	250	358	492	1340
B-300	1200	300	420	612	1540
B-350	1300	350	515	777	1645
B-400	1300	400	515	777	1645


單瓣式逆止閥 CHECK VALVE



UNITS : mm

MODEL	D	E	L	適用機型
C-050	50	30	17	GT-050
C-065	65	45	19	GT-065
C-080	80	55	20	GT-080
C-100	100	70	20	GT-100
C-125	125	90	23	GT-125
C-150	150	110	24	GT-150
C-200	200	140	28	GT-200
C-250	250	190	28	GT-250


雙瓣式逆止閥 DUAL CHECK VALVE



UNITS : mm

MODEL	A	L	適用機型
DC-200	270	127	GT-200
DC-250	332	146	GT-250
DC-300	377	181	GT-300
DC-350	420	184	GT-350
DC-400	483	191	GT-400


充油式壓力錶 LIQUID FILLED PRESSURE GAUGE



UNITS : mm

MODEL	A	B	適用機型
AC-A	63	133.5	GT-50~400
壓力範圍	76~0cmHg, 0~1kg/cm ²		


管接頭 TUBE CONNECTOR



UNITS : mm

MODEL	A	B	C	L	適用機型
V-050	95	2"	50	40	GT-050
V-065	95	2.5"	65	40	GT-065
V-080	95	3"	80	40	GT-080
V-100	95	4"	100	40	GT-100
V-125	155	5"	125	50	GT-125
V-150	155	6"	150	50	GT-150
V-200	155	8"	200	60	GT-200
V-250	155	10"	250	60	GT-250
V-300	155	12"	300	60	GT-300
V-350	160	14"	350	70	GT-350
V-400	160	16"	400	70	GT-400


避震器 ABSORBER



UNITS : mm

MODEL	A	B	C	D	E	F	適用範圍 (kg)
UJ-200J	142	110	65	55	3/8"	Ø12	0~150
UJ-500J	214	166	100	57	1/2"	Ø14	140~450
UJ-800J	285	220	130	80	1/2"	Ø17	400~750

避震墊 ABSORBER



UNITS : mm

MODEL	A	B	C	D	E	F
GT-040	15	25	50			
GT-050~065	15	25	75			
GT-080~100	25	39	102			
GT-125~400				101	147	10



高豐魯氏鼓風機

GOLDENTECH ROOTS BLOWER **ROOTS TYPE BLOWER & VACUUM PUMP**

訂製資料 INQUIRY

當訂製高豐三葉魯氏鼓風機時，請告知以下事項：

1. 用途：例如廢水處理、氣體輸送、電鍍攪拌。
2. 規格：說明風量、出入口狀態（溫度、壓力、濕度）。
3. 驅動方式：馬達型式、轉速、頻率。
4. 安裝情況：室內或室外，週圍的溫度及落塵狀態等。
5. 輸送氣體種類：氣體名稱、化學性質、比重、及是否具有腐蝕性或爆炸性。
6. 附件：說明選用之附件。

When inquiring about GOLDENTECH three lobes rotary blowers , please inform us as followings :

1. Applications : water aeration pneumatic conveying etc.
2. Specifications : suction capacity temperature pressure and humidity.
3. Drive : motor type r.p.m. and frequency.
4. Installations : whether indoors or outdoors , ambient temperature.
5. Type of gas : name character corrosiveness specific gravity.
6. Accessories : remark accessories which to be used.



ISO 9001 認證通過

高豐機械有限公司

GOLDENTECH MACHINERY INDUSTRY CO.,LTD.

高雄公司: 高雄市仁武區鳳仁路97-9號

TEL.: 886-7-373-9820

FAX.: 886-7-373-5225

<http://www.goldentech.com.tw>

E-mail: goldentech67@xuite.net